

Lounge light

SLD – 34/SP

The edge illumination signs us technology that is friendly towards the environment due to its small consumption from the mains power supply. Each model combines modern esthetics and technological functionality. They are used in every area where public orientation and esthetics must be combined. These luminaires can be used as maintained illuminated signs. They consist of two pieces, the illuminated sign with LEDs and the control circuit which is placed on the ceiling or the wall. They can also be recess mounted on a suspended ceiling using the mounting springs contained in the package.



In models SLD-xx/SP, the new adjustable lighted legend mounting device, permits the mounting of the unit on walls or ceilings. By using the special extension rods (20, 40cm), the units can also be mounted at a distance from the ceiling. Recess mounting on a suspended ceiling can be accomplished if the special mounting springs (contained in the package) are used.

Main features include:

- The smallest profile on the market (only 1,5cm)
- Double sided markings
- LEDs – 55/55lm
- 3 hours duration
- High luminosity white LEDs with a great life span
- Surface or recess mounting capability
- TEST button
- Charge indication
- Markings according to EN-1838
- Produced in accordance with European norms EN 60598-1, EN 60598-2-22

For further information contact:

GS Lighting Ltd., United Kingdom, Tel: 01259 760688, Fax: 01259 760088

Email: led@gsighting.co.uk

Web: www.gsighting.co.uk